

Power Supply PS/2 AC Input AT Type

ACE-932A

300W



Specifications

| Input Type | 85 ~ 130 VAC, 180 ~ 265 VAC Auto Range | | | | | |
|------------------|---|------|----------------|-------|-------|--------|
| Output Voltage | +3.3 V | +5 V | +12 V | -5 V | -12 V | +5 Vsb |
| | 33A (3 A min) | | 8A (0.2 A min) | 0.5 A | 3 A | |
| Efficiency | 68 % | | | | | |
| Temperature | Operating : 0 °C ~ 50 °C (50 °C ~ 70 °C derating curve) Storage : -40 °C ~ 75 °C | | | | | |
| MTBF(hrs) | 120,000 | | | | | |
| Output Connector | P8+P9 x1, Extra +5V(P10) x1, HDD/CDROM x4, FDD x2 | | | | | |

Ordering Information

| Part No. | Description |
|---------------|----------------------------------|
| ACE-932A-S-RS | 300 W AC-DC PS/2 AT Power Supply |

ACE-925A/AP

200W



PFC



Specifications

| Input Type | 85 ~ 265VAC Full Range | | | | | |
|------------------|--|------|----------------|-------|-------|--------|
| Output Voltage | +3.3 V | +5 V | +12 V | -5 V | -12 V | +5 Vsb |
| | 22 A (1A min) | | 7 A (0.1A min) | 0.5 A | 0.7 A | |
| Efficiency | 68 % | | | | | |
| Temperature | 0 °C ~ 50 °C (Operating), -40 °C ~ 75 °C (Storage) | | | | | |
| MTBF(hrs) | 130,000 (ACE-925A), 140,000 (ACE-925AP) | | | | | |
| Output Connector | P8+P9 x1, HDD/CDROM x5, FDD x2 | | | | | |

Ordering Information

| Part No. | Description |
|--------------|--|
| ACE-925A-RS | 200 W AC-DC PS/2 AT Power Supply |
| ACE-925AP-RS | 200 W AC-DC PS/2 AT Power Supply, with PFC |

ACE-925M

200W

Medical



Specifications

| Input Type | 90 ~ 264VAC Full Range | | | | | |
|------------------|---|------|--------------|-------|-------|--------|
| Output Voltage | +3.3 V | +5 V | +12 V | -5 V | -12 V | +5 Vsb |
| | 22 A (4A min) | | 7 A (1A min) | 0.5 A | 0.5 A | |
| Efficiency | 65 % | | | | | |
| Temperature | Operating : 0 °C ~ 70 °C (40 °C ~ 70 °C derating curve) Storage : -40 °C ~ 75 °C | | | | | |
| MTBF(hrs) | 110,000 | | | | | |
| Output Connector | P8+P9 x1, HDD/CDROM x5, FDD x2 | | | | | |

Ordering Information

| Part No. | Description |
|-------------|---|
| ACE-925M-RS | 200 W AC-DC PS/2 AT Power Supply, meet Medical standard |

ACE-920A

150W



Specifications

| Input Type | 85 ~ 265VAC Full Range | | | | | |
|------------------|---|------|----------------|-------|-------|--------|
| Output Voltage | +3.3 V | +5 V | +12 V | -5 V | -12 V | +5 Vsb |
| | 20 A (1A min) | | 4 A (0.1A min) | 0.5 A | 0.5 A | |
| Efficiency | 68 % | | | | | |
| Temperature | 0 ~ 50 °C (Operating), -40 °C ~ 75 °C (Storage) | | | | | |
| MTBF(hrs) | 160,000 | | | | | |
| Output Connector | P8+P9 x1, HDD/CDROM x3, FDD x2 | | | | | |

Ordering Information

| Part No. | Description |
|-------------|----------------------------------|
| ACE-920A-RS | 150 W AC-DC PS/2 AT Power Supply |